

Specifications

B2031A		B2030A
Audio Inputs		
XLR connector	servo-balanced input	
¼" TRS	servo-balanced input	
Input impedance	10 kΩ	
Max. input level	+22 dBu	
Components		
Tweeter	1" ferrofluid-cooled dome	¾" ferrofluid-cooled dome
Woofers	8 ¾" polypropylene diaphragm	6 ¾" polypropylene diaphragm
Amplifier		
RMS @ 0.1 % THD	140 W	70 W
Peak power	265 W	125 W
Crossover		
Type	active, 4th order Linkwitz-Riley	
Crossover frequency	2 kHz	
System Specification		
Frequency response	50 Hz to 21 kHz	50 Hz to 21 kHz
Sound pressure level	max. 116 dB SPL @ 1 m (pair)	max. 113 dB SPL @ 1 m (pair)
Power Supply		
Voltage/Fuses		
100 - 120 V~, 50/60 Hz	T 5.0 A H 250 V	T 2.0 A H 250 V
220 - 230 V~, 50/60 Hz	T 2.5 A H 250 V	T 1.6 A H 250 V
Voltage/Supply Current		
100 - 120 V~, 50/60 Hz	max. 2.0 A	max. 1.0 A
220 - 230 V~, 50/60 Hz	max. 1.1 A	max. 0.5 A
Mains Connection		
	Standard IEC connector	
Dimensions/Weight		
Dimensions (H x W x D)	400 x 250 x 290 mm (15 ¾ x 9 13⁄16 x 11 ¾")	317 x 214 x 211 mm (12 ½ x 8 2⁄5 x 8 1⁄3")
Weight	14 kg (31 lbs)	9 kg (20 lbs)