



Bowers & Wilkins

606 S3

Technical Information



Technical features	Decoupled Double Dome Titanium tweeter Continuum™ cone bass / midrange Flowport™
Description	2-way vented-box system
Drive units	1x ø25mm (1 in) Titanium Dome high-frequency 1x ø165mm (6.5 in) Continuum cone bass / midrange
Frequency range	-6dB 40Hz - 33kHz
Frequency response (+/-3dB from reference axis)	52Hz - 28kHz ±3dB
Sensitivity (on axis at 2.83Vrms at 1m)	88dB
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m on axis) <1% 100Hz - 22kHz <0.5% 150Hz - 12kHz
Nominal impedance	8Ω (minimum 3.7Ω)
Recommended amplifier power	30W - 120W into 8Ω on unclipped programme
Max. recommended cable impedance	0.1Ω
Dimensions	Height: 344 mm (13.6 in) cabinet only Width: 189 mm (7.4 in) cabinet only Depth: 300 mm (11.8 in) cabinet only 328 mm (12.9 in) including grille and terminals
Net weight	7.05kg (15.5lbs)
Finishes	Cabinet: Black White Oak Red Cherry (APAC only) Grille: Black (Black and Red Cherry) Grey (White and Oak)