



## Features

Meet the new XLS DriveCore 2 Series. The next generation of XLS got a makeover with a sleek new look, larger LCD display, and more DSP with extended functionality. Like its predecessor, the new XLS is ultra-efficient with Crown's patented DriveCore technology and can drive 2400W at 4Ω bridged with tons of headroom guaranteeing a clean, undistorted signal straight to your speakers. The XLS DriveCore 2 assures that you will be heard as you deliver powerful, pure sound experiences for any venue.

- Class D amp with Crown's ultra-efficient DriveCore technology weighs less than 11 lbs (5 kg)
- Higher DSP capabilities: More control; has band pass filter per channel
- Increased lighting functionality; turn off display or any/all LED indicators except clip and thermal to reduce distraction in dark venues
- Selectable input sensitivity; 1.4Vrms and .775Vrms options so that amp can be driven at full power
- Set display sleep mode after specified time without having to press a button
- Security setting disables menu buttons; menu locked/unlocked by entering button combination
- System reset allows factory settings to be restored
- Remote power trigger
- Peakx™ Limiters provide maximum output while protecting your speakers
- XLR, 1/4", RCA inputs provide flexibility
- Integrated PureBand™ Crossover System for better performance and control
- Efficient forced-air fans prevent excessive thermal buildup

# XLS DriveCore™ 2 Series



XLS 2502

## Power Matrix

| Model | Channels | 2Ω Dual | 4Ω Dual | 8Ω Dual | 4Ω Bridged | 8Ω Bridged |
|-------|----------|---------|---------|---------|------------|------------|
| 1002  | 2        | 550W    | 350W    | 215W    | 1100W      | 700W       |
| 1502  | 2        | 775W    | 525W    | 300W    | 1550W      | 1050W      |
| 2002  | 2        | 1050W   | 650W    | 375W    | 2100W      | 1300W      |
| 2502  | 2        | 1200W   | 775W    | 440W    | 2400W      | 1550W      |

\*Maximum average power in watts at 0.5% THD, 1kHz

| Performance Specifications                                                        | XLS 1002                            | XLS 1502                            | XLS 2002                            | XLS 2502                            |
|-----------------------------------------------------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|
| Sensitivity                                                                       | .775Vrms or 1.4Vrms                 | .775Vrms or 1.4Vrms                 | .775Vrms or 1.4Vrms                 | .775Vrms or 1.4Vrms                 |
| Frequency Response (at 1W, 20Hz to 20kHz)                                         | +0dB, -1dB                          | +0dB, -1dB                          | +0dB, -1dB                          | +0dB, -1dB                          |
| Signal to Noise Ratio (rated as dBr to full rated 8Ω power output; A-Weighted)    | >97dB*                              | >103dB*                             | >103dB*                             | >103dB*                             |
| Total Harmonic Distortion (THD)                                                   | <0.5%                               | <0.5%                               | <0.5%                               | <0.5%                               |
| Intermodulation Distortion (60Hz and 7kHz at 4:1) from full rated output to -30dB | <0.3%                               | <0.3%                               | <0.3%                               | <0.3%                               |
| Damping Factor (8Ω, 10Hz ~ 400Hz)                                                 | >200                                | >200                                | >200                                | >200                                |
| Crosstalk (below rated 8Ω power)                                                  | At 1kHz: > 85dB<br>At 20kHz: > 55dB | At 1kHz: > 85dB<br>At 20kHz: > 55dB | At 1kHz: > 85dB<br>At 20kHz: > 55dB | At 1kHz: > 85dB<br>At 20kHz: > 55dB |

## Physical Specifications

|                 |                   |                   |                    |                    |
|-----------------|-------------------|-------------------|--------------------|--------------------|
| Width           | 19 in. (48.3 cm)  | 19 in. (48.3 cm)  | 19 in. (48.3 cm)   | 19 in. (48.3 cm)   |
| Height          | 3.5 in. (8.9 cm)  | 3.5 in. (8.9 cm)  | 3.5 in. (8.9 cm)   | 3.5 in. (8.9 cm)   |
| Depth           | 7.7 in. (19.6 cm) | 7.7 in. (19.6 cm) | 10.7 in. (27.2 cm) | 10.7 in. (27.2 cm) |
| Net Weight      | 8.6 lbs (3.9 kg)  | 8.6 lbs (3.9 kg)  | 10.8 lbs (4.9 kg)  | 10.8 lbs (4.9 kg)  |
| Shipping Weight | 13.6 lbs (6.2 kg) | 13.6 lbs (6.2 kg) | 15.8 lbs (7.2 kg)  | 15.8 lbs (7.2 kg)  |

\*At .775Vrms sensitivity, Signal to Noise is 6dB lower.

Specifications subject to change without prior notice. Latest information available at [www.crownaudio.com](http://www.crownaudio.com). Crown offers a three-year, no-fault, fully transferable warranty for every new Crown amplifier – an unsurpassed industry standard. With this unprecedented no-fault protection, your new Crown amplifier is warranted to meet or exceed original specifications for the first three years of ownership. During this time, if your amplifier fails, or does not perform to original specifications, it will be repaired or replaced at our expense. In most cases, the only things not covered by this warranty are those losses normally covered by insurance and those caused by intentional abuse. Plus, the coverage is transferable, should you sell your amplifier. See your authorized Crown dealer for full warranty disclosure and details. For customers outside of the USA, please contact your authorized Crown distributors for warranty information or call 574-294-8200. © 2015 Crown Audio®, Inc.