



EVID

C O M P A C T S O U N D

SUPERB SOUND MADE SIMPLE

 **Electro-Voice**



**SUPERB
SOUND
MADE
SIMPLE**

FLEXIBLE, SCALABLE BACKGROUND MUSIC (BGM) SOLUTION FOR A WIDE RANGE OF ARCHITECTURAL ENVIRONMENTS, INCLUDING RETAIL SPACES, OFFICES, AND RESTAURANTS.

FIVE INTERCHANGEABLE MODELS OFFER FLEXIBLE COMBINATIONS FOR BIGGER SOUND, SMALLER SIZE, AND EASY INSTALLATION

The new EVID Compact Sound speaker series joins the globally popular EVID (EV Innovative Design) family of small-format installed audio products from Electro-Voice.

EVID Compact Sound is designed to offer an unparalleled performance-to-size ratio in the small-format installed sound category. The series includes five sonically and aesthetically matched models which allow complete systems to be customized more effectively and more economically: subwoofer and satellite speakers for surface-mounting, subwoofer and satellite speakers for ceilings, and a pendant speaker.

Individual models may be mixed with one another for optimal results according to application, and all stand apart from other available products by providing a unique combination of superior EV sound quality, stylish design, smaller size, and simpler installation.



“

BALANCED CROSSOVER CIRCUITS

SEAMLESSLY BLEND THE OUTPUT OF THESE HIGH-QUALITY LOUSPEAKERS SO THAT THE AUDIO SYSTEM SEEMS TO DISAPPEAR, LEAVING ONLY THE MUSIC.

”

SUPERB SOUND MADE SIMPLE

For more information, visit www.electrovoice.com



COMMON SYSTEM FEATURES

- “BGM” in a box: Purchase either a complete pre-packaged system or mix-and-match satellite models with any subwoofer to meet décor or installation requirements.
- Direct connection of satellites to subwoofer — substantially simplifies wiring.
- Subs feature a large 8” woofer for increased LF output and more pleasing sound at lower volumes.
- Supports 100 W, 70/100 V, and 4/8 ohm audio connections.



SURFACE-MOUNT FEATURES

- Simplified mounting design for satellites — enables quicker installation while allowing for significant articulation and range of motion.
- Attractive subwoofer design with full-face grille — blends in to environment.
- Supports stereo operation with 8-ohm audio connections.
- Quick-mount slide-on wall bracket included.
- Compact sub and satellites offer surprising performance-to-size ratio.
- Available in black or white finishes.



Ceiling sub input panel



Ceiling sub grille off



Surface sub wall-bracket mount



CEILING FEATURES

- Quick-install design with captive mounting tabs to fit nearly any ceiling construction.
- Four-pin Phoenix connectors on ceiling satellite speakers support pass-thru wiring.
- UL 2043/1480 ratings allow for use in signaling applications and plenum air spaces.
- Ceiling cutout templates and all mounting accessories included.
- Available in white finish.

* Products not shown to scale.



PENDANT-MOUNT FEATURES

- 2" full-range transducer — acoustically matched to ceiling and surface-mount satellite versions.
- Attractive compact design.
- Concealed wire connection with pass-thru Phoenix plug for easy wiring.
- UL-rated quick-mount pendant cable included.
- Designed to be exclusively used with either the Compact Sound Ceiling or Surface mount subwoofers.
- Available in white finish.



Surface sub input panel



Surface satellite wall-bracket arm



Surface satellite input panel

SUPERB SOUND MADE SIMPLE

SPECIFICATIONS	EVID 40S (surface-mount sub)	EVID 2.1 (surface-mount satellite)	EVID 40C (ceiling sub)	EVID C2.1 (ceiling satellite)	EVID P2.1 (pendant mount)
Frequency Response (-10 dB)	42 Hz – 300 Hz	180 Hz – 20 kHz	45 Hz – 300 kHz	180 Hz – 20 kHz	180 Hz – 20 kHz
Power Handling	200 W	30 W	200 W	30 W	30 W
Sensitivity	88 dB	84 dB	88 dB	84 dB	84 dB
Impedance	Dual 8 ohm / mono 4 ohm	16 ohms	mono 4 ohms	16 ohms	16 ohms
Maximum SPL	114 dB	100 dB	114 dB	100 dB	100 dB
Voice Coverage (H x V)	Omnidirectional	150° x 150°	Omnidirectional	150° x 150°	150° x 150°
Music Program Coverage (H x V)	Omnidirectional	100° x 100°	Omnidirectional	100° x 100°	100° x 100°
Transducer	200 mm (7.87 in)	50 mm (1.97 in)	200 mm (7.87 in)	50 mm (1.07 in)	50 mm (1.07 in)
Bracket Adjustment Range (H x V)	Fixed	160° x 60°	N/A	N/A	N/A
Connectors	Phoenix (2-pin)	Phoenix (2-pin)	Phoenix (2-pin)	Phoenix (4-pin)	Phoenix (4-pin)
Enclosure	Wood (MDF)	ABS (fire rated)	Steel & ABS (fire rated)	Steel & ABS (fire rated)	ABS (fire rated)
Transformer Taps	100 W, 50 W, 25 W, 12.5 W	N/A	100 W, 50 W, 25 W, 12.5 W	N/A	N/A
Dimensions (H x W x D)	400 mm x 400 mm x 230 mm (15.75 in x 15.75 in x 9.06 in)	115 mm x 85 mm x 95 mm (4.53 in x 3.35 in x 3.75 in)	316 mm x 373 mm (12.44 in x 14.69 in)	119 mm x 135 mm (4.7 in x 5.3 in)	201 mm x 113 mm (7.92 in x 4.45 in)
Net Weight (Individual Units)	12.05 kg (26.55 lb)	0.5 kg (1.1 lb)	9.52 kg (21 lb)	0.82 kg (1.8 lb)	0.73 kg (1.6 lb)
Shipping Weight	1 sub and 4 satellites: 18.26 kg (40.25 lb)		1 sub and 4 satellites: 19.05 kg (42 lb)		2.04 kg (4.5 lb) per pair
Included Accessories	Wall bracket; hex wrench	Wall bracket; hex wrench	C-Ring, Tile Rails	C-Ring	Suspension cable

EVID COMPACT SOUND



Headquarters Americas:
 Bosch Security Systems, Inc.
 12000 Portland Ave South | Burnsville, MN 55337 | USA
 Ph: 1 800 289 0096 | Fax: 1 800 955 6831
buv.orders@us.bosch.com