

XT1200A



- Full-power control over-current protection mechanism.
- Due to short circuit protection mechanism, rapid response, turn off output power.
- Unique output pressure limit is set to ensure that the amplifier does not appear square wave signal.

SPECIFICATIONS

MODEL	XT12000A
Stereo (Channels)	4 CH
8Ω / FTC 20Hz-20kHz @0.5% THD	4x1000W
4Ω / FTC 20Hz-20kHz @0.5% THD	4x1200W
2Ω / FTC 20Hz-20kHz @0.5% THD	4x1600W
Bridged (2/1 Channels)	Power
8Ω / FTC 20Hz-20kHz @0.1% THD	2x2000W
4Ω / FTC 20Hz-20kHz @0.1% THD	2x2400W
S/N (20Hz-20KHz) 8Ω	98dB
THD (@8Ω 1KHz)	<0.5%
Input Impedance	20KΩ
Frequency Response	20Hz-20KHz
Circuit Type	CLASS H
Damping Factor	>600 @8Ω
Cooling System	2 Fans
In/Output Connection	Balance Female XLR
Control	Volume Control for each channel. Stereo/Parallel/Bridge, Bridge Denote, Low cut
Indicator light	POW:ACTIVE, SIG:SIGNAL, PRO:PROTECT, CLIP
Protection	Short, Auto Limited, Overload, AC/DC protection
Dimension (W x D x H)	555 x 470 x 140mm
Power Supply	220V (Default), 110V (Could be customized)

