

SOLO6

Product sheet

MADE IN
FRANCE

Solo6 is a 2-way monitor offering transparency, a level of definition, dynamics and soundstage precision that is unrivalled in its price range. Thanks to its Focus full-range mode, Solo6 is two monitors in one, where the woofer alone becomes a full-range speaker driver.



Key points

- Beryllium inverted dome tweeter: very low directionality, excellent linearity and dynamics
- Optimised baffle tweeter: excellent dispersion control
- Composite sandwich 'W'-cone: sound neutrality, no distortion
- Focus mode: two monitors in one; 2-way monitor and 1-way full-range monitor (woofer alone)
- Large laminar port: no port noises or distortion
- Inserts for wall fastening
- Automatic disengageable stand-by mode
- Settings: activatable/deactivatable, LF shelving, HF shelving, LMF @ 160Hz

Type	2-way monitor
Frequency response (@ -3dB)	40Hz - 40kHz
Focus mode	110Hz - 10kHz
Maximum SPL (Average CEA2034 50-10kHz free field @ 1m)	110dB
Focus mode (Average CEA2034 100-10kHz free field @ 1m)	109.5dB
Input	Balanced XLR 10 kΩ
Bass amplifier stage	80W RMS
Treble amplifier stage	50W RMS
Nominal power supply	-100-120 VAC/220-240 VAC 50/60Hz

User controls	Sensitivity, stand-by HPF, LF Shelv, LMF EQ, HF Shelv
Fuses	-100-120V, T2.5AL/250V -220-240V, T1.25AL/250V
Bass	6.5" (16.5cm) "W" cone
Treble	1.5" (38mm) Beryllium
Shielding	no
Construction	7/8" (22mm) MDF
Finish	Dark red natural veneering side panels, black body
Dimensions (HxWxD)	13 1/8" x 9 3/4" x 11 5/8" (33.4x24.6x29.5cm)
Weight	28.6lbs (13kg)
Temperature range	During use: 5-35°C In storage: 0-50°C
Wall mounting	K&M® 24471 fixing kit + K&M® 24359 adapter
Ceiling mounting	K&M® 24496 fixing kit K&M® 24491 fixing kit + K&M® 24359 adapter

*Caution: wall and/or ceiling mounting is risky, please refer to the user manual