

24-Port Gigabit PoE+ Smart Switch with 2 SFP Ports and Cloud Management



Going Gigabit and PoE+ Just Got More Cost-Effective!

As a leading provider of network equipment for SMBs, NETGEAR® understands the importance of providing great choice of PoE port counts and power budgets that can adapt to the business's needs, whether in the hospitality, catering, education or retail domains.

The GS724TP and GS724TPP 24-Port Gigabit Switch with PoE+ and 2 SFP Ports join the NETGEAR Standalone Smart Switches family, adding full 24 port PoE+ support for deployment of modern high-power PoE devices. Cautious spender organizations can now deploy denser PoE+ devices connected to a cost-effective switch, with a reasonable PoE power

budget of 190W (GS724TP) or 380W (GS724TPP).

NETGEAR Smart Switches offer powerful Layer 2 features, great PoE functionality, and enhanced performance and usability. These switches are the ideal solution even for the most advanced small and medium organizations looking for the best combination of features, performance, and value: they are purposely designed for converged networks where voice, video, data are all carried on a single network platform. Temperature- and load-based fan-speed control combines accurate monitoring with minimized system acoustic noise: the GS724TP and

GS724TPP support quiet rack mounting operation with a maximum of 26.1 dBA (GS724TP) and 33.6 dBA (GS724TPP) even at full power and 25°C (77°F) ambient.

To empower the PoE applications, NETGEAR Insight Remote/Cloud Management is added to these two new switch models as an optional management mode. By activating the NETGEAR Insight Cloud management, the users will enable management features allowing businesses simpler configuration and deployment from anywhere using the NETGEAR Insight app from mobile devices or the Insight Cloud Portal from any device with a web browser.

Highlights

More Powerful Switch for High Power Devices

- 24 x PoE+ Gigabit ports with 190W PoE budget (GS724TP) or 380W PoE budget (GS724TPP)
- 2 dedicated Gigabit SFP fiber uplink ports

Fast and flexible solution for SMB data, voice and video converged network

- Non-blocking switching with 52Gbps
- Flexible rack-mounting option

Powerful Connectivity and Security

- Advanced VLAN support for better network segmentation

- L2/L3/L4 access control lists (ACLs) for granular network access control including 802.1x port authentication
- Advanced per port PoE controls for remote power management of PoE connected devices including operation scheduling

24-Port Gigabit PoE+ Smart Switch with 2 SFP Ports and Cloud Management

- Advanced QoS (Quality of Service) for traffic prioritization including port-based, 802.1p and L2/L3/L4 DSCP-based
- Auto “denial-of-service” (DoS) prevention
- IGMP Snooping and Querier for multicast optimization
- Egress Rate limiting and priority queuing for better bandwidth allocation
- Port mirroring for network monitoring
- Energy Efficient Ethernet (IEEE 802.3az) for maximum power savings
- IPv6 management: IPv6 QoS, IPv6 ACL, IPv6 Multicast, and static and dynamic IPv6 address assignment
- Cable test to troubleshoot connection issues

- Easy-to-use Web browser-based management GUI available in English, German and Japanese
- SNMP v1, v2c, v3 and RMON remote monitoring

Fully-integrated cloud-manageable devices

Remote/Cloud Management capability with NETGEAR Insight. Instantly activate NETGEAR Insight Cloud management from the web GUI, for simpler configuration and deployment from anywhere using the NETGEAR Insight app on mobile devices or the Insight Cloud portal through a web browser

Smart IT, not Big IT

- NETGEAR Insight remote/cloud management, monitoring and maintenance using the NETGEAR Insight mobile app or Insight Cloud Portal for network-level management

- NETGEAR Switch Discovery Tool (NSDT) to discover, register and access to the local browser interface to configure the switches
- Network Management System (NMS300), allowing all NETGEAR business products to be deployed and managed through this single interface
- Text-based Lite Command-line Interface (CLI)

NETGEAR Quality and Reliability

- Worry-free Limited Lifetime Warranty*, online technical chat support and Next Business Day (NBD) replacement.
- 90-days Free 24x7 Advanced Technical Phone Support**



24-Port Gigabit PoE+ Smart Switch with 2 SFP Ports and Cloud Management

Hardware at a Glance

	FRONT				REAR	SIDE
Model Name	Form-Factor	10/100/1000BASE-T RJ-45 Copper Ports	1G SFP Uplink	PoE+ 802.3 at Ports (Budget)	Power Supply (PoE Budget)	Fans
GS724TP	Rack mount	24	2	24 (190W)	1 internal PSU, fixed	2 internal fans, fixed
GS724TPP	Rack mount	24	2	24 (380W)	1 internal PSU, fixed	2 internal fans, fixed

Software at a Glance

LAYER 2+ / LAYER 3 Lite FEATURES							
Device Management	Network-wide Management (Insight Management)	PoE Control Features	IPv4/IPv6 ACL and QoS	IPv4/IPv6 Multicast Filtering	VLANs	Convergence	Link Aggregation
Web Browser-based GUI (HTTP/HTTPS) Text-based Lite Command-line Interface (CLI) RMON, SNMP NETGEAR Insight mobile app or Insight Cloud Portal for local/remote/anywhere management from your mobile device, PC, Mac, or tablet	Centralized network configuration (policies) Auto-join & configure (zero-touch provisioning) Multisite, multi-network single pane-of-glass view Multi-switch/multi-port concurrent configuration	PoE on/off Dynamic PoE budget allocation PoE power priority setting PoE Power Usage Metering PoE scheduling	L2, L3, L4, ingress	IGMP Snooping, Querier	Static, Dynamic, VoIP, Voice, 16K Max MAC (256 VLANs)	LLDP-MED, RADIUS, 802.1X	LACP and Manual Static LAGs (up to 16 LAGs with max 8 members)

Performance at a Glance

Model Name	Packet buffer	CPU	ACLs	MAC Address Table VLANs	Fabric	Latency (64-byte packets)	Multicast IGMP Groups
GS724TP	1.5MB	800MHz ARM A55 Single Core 512MB RAM 64MB FLASH	100 shared (ingress)	16K MAC 256 VLANs	52 Gbps line-rate	1G Copper: < 3.749 µs; 1G Fiber: < 3.129 µs	512
GS724TPP						1G Copper: < 3.563 µs; 1G Fiber: < 2.574 µs	

24-Port Gigabit PoE+ Smart Switch with 2 SFP Ports and Cloud Management

Features and Benefits

Hardware Features	
Fully-integrated Cloud-manageable Devices	Require no additional hardware (cloud keys, network portals, local servers, VPN or proxy appliances etc) to directly connect to the cloud and allow remote management. No additional hardware or software. Just switch to Insight Cloud Management mode through Web browser-based User Interface and go.
1000BASE-T Copper Ethernet PoE+ connections	Support high-density VoIP, Surveillance and Wi-Fi AP deployments, scalable for future growth. Never face the risk of running out of PoE ports.
1000BASE-X Fiber SFP ports	Two dedicated Gigabit SFP ports for aggregation to the network core. Support for Fiber and Copper modules.
Low Acoustics	Temperature- and load-based fan-speed control allow for quiet operation in both desktop or rack mount configuration.
Energy Efficient Ethernet (IEEE 802.3az)	Maximum power reduction for ongoing operation cost savings.
Desktop and rack mount (kit available)	Flexible deployment on desktop and also support rack mount.
Kensington Lock Slot	Prevent theft, removal, or tampering when used for desktop deployment.
Software Features	
Remote setup, management, and monitoring anywhere, anytime, from your mobile device, PC, Mac, or tablet	Locally or remotely setup, configure, manage, monitor or even trouble-shoot your network from anywhere, anytime. Check network status, view dashboards for network health and activity, power cycle PoE ports, etc, and update firmware remotely. No need to be on-site, open up ports to your network, or VPN into it.
Auto-join and Configure (Zero-Touch Provisioning)	Additional Insight Managed devices added to the network automatically inherit settings and configuration.
Multi-site, Multi-network Single Pane-of-Glass View	View and configure multiple networks across multiple sites, all from one single app; NETGEAR Insight.
Text-based Lite Command-line Interface (CLI)	Provides a text-based way to manage and monitor the system. The CLI can be accessed by using a direct serial connection, or by using a remote logical connection with telnet or SSH.
Comprehensive IPv6 Support for Management, ACLs and QoS	Build current network with future in mind. Ensure investment protection and a smooth migration to an IPv6-based network without switch replacement.
Robust security features: • 802.1x authentication (EAP) • Port-based security by locked MAC	Build a secured, converged network with all types of traffic by preventing external attacks and blocking malware while allowing secure access for authorized users.
Comprehensive QoS features: • Port-based or VLAN 802.1p-based prioritization • Layer 3-based (DSCP) prioritization • Port-based egress rate limiting	Advanced controls for optimized network performance and better delivery of mission-critical traffic such as voice and video.
Auto-VoIP and Auto-Voice VLAN	Automatic Voice over IP prioritization (Auto-VoIP) simplifies most complex multi-vendor IP telephone deployments either based on OUI bytes (default database and user-based OUIs) in the phone source MAC address, providing the best class of service to VoIP streams (both data and signaling) over other ordinary traffic by classifying traffic, and enabling correct egress queue configuration.
IGMP Snooping	Facilitate fast receiver joins and leaves for multicast streams. Save cost and improve network efficiency by ensuring multicast traffic only reaches designated receivers without the need of an extra multicast router.

24-Port Gigabit PoE+ Smart Switch with 2 SFP Ports and Cloud Management

Features and Benefits

Software Features	
Protected Ports	Ensure no exchange of unicast, broadcast, or multicast traffic between the protected ports on the switch, thereby improving the security of your converged network. This allows your sensitive phone conversations to stay private and your surveillance video clips can be forwarded to their designated storage device without leakage or alteration.
DHCP Snooping	Ensure IP address allocation integrity by only allowing DHCP messages from trusted DHCP servers and dropping malformed DHCP messages with a port or MAC address mismatch.
Dynamic VLAN Assignment (RADIUS)	IP phones and PCs can authenticate on the same port but under different VLAN assignment policies. Users are free to move around and enjoy the same level of network access regardless of their physical location on the network.
Link Aggregation (LACP)	Build up bigger bandwidth to support aggregated uplink/downlink traffic or to provide redundant link(s). Aggregate up to 8 ports for 8Gbps connections.
PoE Timer and Scheduling	Allows IT administrators to increase network security, better utilize network resources and conserve energy by scheduling or remotely controlling on/off of PoE ports.
Port Mirroring and Cable Test	Many-to-one port mirroring for better and quicker network diagnostics and troubleshooting. Cable test easily identifies bad Ethernet cables.
Dual Firmware Images	Dual firmware images for transparent firmware updates with minimum service interruption
Firmware Updates from Cloud	Direct cloud-to-device firmware updates, initiated and/or scheduled using the Insight app, all from the palm of your hand, anytime, anywhere!

24-Port Gigabit PoE+ Smart Switch with 2 SFP Ports and Cloud Management

Simply Activate NETGEAR Insight Cloud Management to manage your network. Anytime. Anywhere.

By activating the NETGEAR Insight Cloud management, the users will enable fundamental management features allowing businesses simpler configuration and deployment from anywhere using the NETGEAR Insight app from mobile devices or the Insight Cloud Portal from any device with a web browser.

Unique advanced management features of these Insight Managed devices include:


- Remote monitoring and management with performance dashboards and troubleshooting features including remote reboot, port and PoE advanced configuration including remote enable/disable/power-cycle, PoE scheduling, and firmware updates with auto-schedule mode
- Single pane-of-glass multi-device, multi-network, and multi-site remote monitoring and notifications with the NETGEAR Insight app
- Full-fledged local or remote access for configuration, management, and monitoring on a larger display using your tablet, laptop, or desktop computer through the NETGEAR Insight Cloud portal
- Configurable in-app and email alerts and notifications
- Auto-join and configure (zero-touch provisioning) for additional Insight devices added to the network
- Centralized network configuration (policies) across Insight Managed Switches, Access Points, and ReadyNAS storage for VLANs, ACLs, QoS, LAGs, etc.
- Cloud-based network administration, monitoring, and firmware management

For more information about NETGEAR Insight-manageable device settings, please see at:
<https://www.netgear.com/support/product/Insight.aspx>

24-Port Gigabit PoE+ Smart Switch with 2 SFP Ports and Cloud Management

Example Application

Power The Devices in Your Business



The new standalone GS724TP and GS724TPP switch are designed with 24 ports PoE+ and 2 SFP ports. With 190W power on GS724TP and 380W power on GS724TPP, the two switches can meet the current and future needs of wireless converged networks. Within small and medium-sized organizations, there is growing adoption of PoE devices such as VoIP phones, IP security cameras, wireless access points, proximity sensors, LED lighting, door locks, and other IoT devices that require network switches capable of supporting dense PoE installations. Wireless access points and pan-tilt-zoom HD cameras using Wave 2 802.11ac Wi-Fi also require PoE+ power (802.3at), increasing the power demands on PoE switches.

“PoE devices are putting a strain on switching power demands.” As a leading provider of network equipment for SMBs, NETGEAR understands the importance of providing great choice of PoE port counts and power budgets that can adapt to the business’s needs, whether in the hospitality, education or retail domains.

These switches provide a great value, with configurable Layer 2 network features like VLANs and PoE operation scheduling. Advanced features such as DiffServ QoS, LACP link aggregation and Spanning Tree will satisfy even the most advanced small business networks. With Insight Cloud management capability, managing those PoE and Smart switching features is just one click away.

24-Port Gigabit PoE+ Smart Switch with 2 SFP Ports and Cloud Management

Technical Specifications		GS724TPv3	GS724TPPv3
Gigabit Ethernet RJ-45 Copper ports (10M/100M/1G) - 1000BASE-T		24	
PoE/PoE+ ports		24	
Gigabit SFP (fiber) ports (100M/1G) - 1000BASE-X		2 (dedicated)	
Power Supply		Internal Power Supply	
Kensington Lock		Yes (rear)	
LEDs			
Front (per device)		Power (with Cloud Mode Indicator), PoE Max, PoE Fault	
Front (per port)		Speed/Link/Activity	
Unified Network Management (Discovery, Setup, Monitoring, and Management) through NETGEAR Insight Cloud Management			
Discovery, setup, monitoring and management		NETGEAR Insight mobile app on phone or tablet; Insight Cloud Portal from PC, Mac, or tablet web browser	
Remote/Cloud management		Anywhere, anytime, from the palm of your hand using Insight mobile app or from any PC, Mac, or tablet web browser using the Insight Cloud Portal	
Centralized network configuration (policies)		Centralized network configuration (policies) across Insight Managed Switches, Wireless Access Points, and Business-class ReadyNAS Storage for VLANs, ACLs, QoS, and LAGs	
Device auto-join and configure (zero-touch provisioning)		Additional Insight Managed devices added to the network automatically inherit the network configuration	
Multi-site, multi-network single pane-of-glass view		Manage multiple sites, locations, and networks in a single view using the Insight mobile app or Insight Cloud Portal	
Multi-switch, multi-port concurrent configuration for ACLs, VLANs, QoS, PoE, etc		Apply settings and policies on multiple ports across multiple switches all at the same time using the Port Config Wizard	
Performance Specification			
CPU		800MHz ARM A55 Single Core 512MB RAM 64MB SPI FLASH	
Packet buffer memory (Dynamically shared across only used ports)		1.5MB	
Forwarding modes		Store-and-forward	
Bandwidth (non-blocking, full duplex)		52 Gbps	
Priority queues		8	
Priority queuing		Weighted Round Robin (WRR) or Strict Priority	
MAC Address database size (48-bit MAC addresses)		8K	
Multicast groups		512	
Number of VLANs		256	
Number of DHCP snooping bindings		256	
Access Control Lists (ACLs)		100 shared for MAC, IP and IPv6 ACLs (ingress)	
Packet forwarding rate (64 byte packet size) (Mfps or Mpps)		38.6	
1G Copper standard latency (µsec) (64-byte; 1518-byte; 9216-byte frames)		64-byte: 3.956 µsec 1518-byte: 4.394 µsec 9216-byte: 4.691µsec	64-byte: 4.001 µsec 1518-byte: 4.398µsec 9216-byte: 4.701 usec

24-Port Gigabit PoE+ Smart Switch with 2 SFP Ports and Cloud Management

Performance Specification	GS724TPv3	GS724TPPv3
1G SFP Fiber latency (µsec) (64-byte; 1518-byte; 9216-byte frames)	64-byte: 1.842 µsec 1518-byte: 1.878 µsec 9216-byte: 1.891 µsec	64-byte: 1.892 µsec 1518-byte: 1.914 µsec 9216-byte: 1.927 µsec
Jumbo frame support	Up to 10K packet	
Acoustic noise level @ 25°C (dBA) (ANSI-S10.12)	26.1 dBA	33.6 dBA
Mean Time Between Failures (MTBF) @ 25°C	1,784,610 hrs (142 yrs)	1,310,422 hrs (149 yrs)
POE Configuration		
Number of PoE (802.3af) / PoE+ (802.3at) ports	24 PoE+	24 PoE+
Total PoE power budget (watts)	190W	380W
Advanced per-port PoE controls (enable/disable/power limit)	Yes	
Advanced per-port PoE scheduling/timers	Yes	
L2 Services - VLANs		
IEEE 802.1Q VLAN tagging	Yes	
Management VLAN	Configurable	
L2 Services - Availability		
Broadcast, multicast, unknown unicast storm control	Yes	
IEEE 802.3ad - LAGs (LACP)	Yes	
IEEE 802.3x (full duplex and flow control)	Yes	
IEEE 802.1D Spanning Tree Protocol	Yes	
IEEE 802.1w Rapid Spanning Tree Protocol	Yes	
IEEE 802.1s Multiple Spanning Tree Protocol	Yes	
L2 Services - Multicast Filtering		
IGMP snooping (v1, v2, and v3)	Yes	
IGMP snooping querier	Yes	
Block unknown multicast	Yes	
Multicast groups	512	
DHCP Services		
DHCP client	Yes	
DHCP snooping	Yes	
Number of DHCP snooping bindings	256	
Link Aggregation		
IEEE 802.3ad - LAGs (LACP)	Yes	
Manual Static LAG	Yes	
# of Static or LACP LAGs	16 LAGs with max 8 members in each LAG	
# of Members in each LAG		

24-Port Gigabit PoE+ Smart Switch with 2 SFP Ports and Cloud Management

Network Monitoring and Discovery Services	GS724TPv3	GS724TPPv3
802.1ab LLDP		Yes
LLDP-MED		Yes
SNMP		v1, v2, v3
RMON group 1,2,3,9		Yes
Network Security		
IEEE 802.1x		Yes (EAP)
Guest VLAN		Yes
RADIUS-based VLAN assignment via .1x		Yes
MAC-based .1x		Yes
RADIUS accounting		Yes
Access Control Lists (ACLs)		L2 / L3 / L4 ingress
IP-based ACLs (IPv4 and IPv6)		Yes
MAC-based ACLs		Yes
TCP/UDP-based ACLs		Yes
MAC lockdown		Yes
MAC lockdown by the number of MACs		Yes
Control MAC # Dynamic learned entries		16,384
Control MAC # Static entries		256
IEEE 802.1x RADIUS port access authentication		Yes
Port-based security by locked MAC addresses		Yes
Broadcast, multicast, unknown unicast storm control		Yes
Protected ports		Yes
DoS attacks prevention		Yes
Quality of Service (QoS)		
Port-based rate limiting		Yes egress
Port-based QoS		Yes
Support for IPv6 fields		Yes
DiffServ QoS		Yes ingress
IEEE 802.1p COS		Yes
Destination MAC and IP		Yes
IPv4 and IPv6 DSCP		Yes
TCP/UDP-based		Yes
Weighted Round Robin (WRR)		Yes
Strict priority queue technology		Yes
Auto-VoIP VLAN / Auto-Voice VLAN	Yes, manual or automatic assignment of VoIP phone traffic based on OUI bytes (default database and user-based OUIs) in the phone source MAC address to Voice VLAN associated with high priority QoS parameters	

24-Port Gigabit PoE+ Smart Switch with 2 SFP Ports and Cloud Management

Other Features	GS724TPv3	GS724TPPv3
Advanced per-port PoE controls (enable/disable/power limit)		Yes
Advanced per-port PoE scheduling/timers		Yes
Loop detection & prevention		Yes, by STP
DNS Client		Yes
Option to enable/disable BPDU flooding when STP is disabled		Yes
Option to enable/disable the flooding of EAPOL when 802.1x is disabled		Yes
Management, Monitoring & Troubleshooting		
Cloud/Remote management		Yes
Insight mobile app & Insight Cloud Portal management		Yes
uPnP Discovery		Yes
Lite Command-line Interface (CLI)	Yes (Refer to Lite CLI Manual on NETGEAR Support page of the switch model)	
Networking monitoring		Yes
Data/performance logs		Yes
Centralized network configuration/policies (network-centric management)		Yes
Device auto-join and configure (zero-touch provisioning)		Yes
Multi-site, multi-network single pane-of-glass view		Yes
Multi-switch, multi-port concurrent configuration		Yes
Network/global password (for all Insight Managed devices on a network)	Yes (per network/subnet via NETGEAR Insight mobile app and Insight Cloud Portal)	
Password management		Yes
IP Access List		Yes
Configurable management VLAN		Yes
Admin access control via RADIUS and TACACS+		Yes
IPv6 management		Yes
SNTP client over UDP port 123		Yes
Firmware upgrade direct from Cloud (via mobile device or Insight Cloud portal)		Yes
SNMP v1/v2c		Yes
SNMP v3 with multiple IP addresses		Yes
RMON group 1,2,3,9		Yes
Port mirroring		Yes
Many-to-one port mirroring		Yes
Cable test utility		Yes
Ping and tracerout client		Yes

24-Port Gigabit PoE+ Smart Switch with 2 SFP Ports and Cloud Management

Management, Monitoring & Troubleshooting	GS724TPv3	GS724TPPv3
Local-only web browser-based management GUI		Yes
HTTP/TLS Web-based access (version)		Yes (1.2)
HTTP firmware upload/download		Yes
Dual software (firmware) image		Yes
Memory and flash log		Yes
Syslog (Server)		Yes
Power Consumption		
Max power (worst case, all ports used, line-rate traffic) (Watts)	20.69W	21.59W
Max power (worst case, all ports used, full PoE, line-rate traffic) (Watts)	231.07W	396.95W
Min power (link-down standby) (Watts)	11.3W	13.3W
Heat Dissipation (max w/full PoE & standby) (BTU/hr)	Max: 739.42 BTU/hr Min: 36.16 BTU/hr	Max: 1270.24 BTU/hr Min: 42.56 BTU/hr
Energy Efficient Ethernet (EEE) IEEE 802.3az	Yes (deactivated by default)	
Auto Power Down	Yes (deactivated by default)	
Fan(s) (temperature- and load-based speed control)	2	
Physical Specifications		
Dimensions (W x D x H)	440 x 257 x 43.2 mm (17.3 x 10.1 x 1.7 in)	440 x 257 x 43.2 mm (17.3 x 10.1 x 1.7 in)
Weight	3.15 kg (6.96 lb)	3.7 kg (8.1 lb)
Mounting options	Desktop, rack mount	Desktop, rack mount
Environmental Specifications		
Operating		
Operating temperature	0° to 50°C (32° to 122°F)	
Humidity (relative)	95% maximum relative humidity (RH), non-condensing	
Altitude	10,000 ft (3,000 m) maximum	
Storage		
Storage temperature	-20° to 70°C (- 4° to 158°F)	
Humidity (relative)	95% maximum relative humidity (RH), non-condensing	
Altitude	10,000 ft (3,000 m) maximum	
Warranty and Support		
Hardware Limited Warranty	Limited Lifetime*	
Next-Business-Day (NBD) Replacement	Limited Lifetime*	
Technical support via phone	90 days free from date of purchase*	
24x7 Online Chat Techninal support	Limited Lifetime*	
ProSUPPORT OnCall 24x7 Service Packs**	Category 1 PMB0311-10000S PMB0331-10000S PMB0351-10000S	

24-Port Gigabit PoE+ Smart Switch with 2 SFP Ports and Cloud Management

Ordering Information

Package Contents	GS724TPv3	GS724TPPv3
Smart Switch	✓	✓
Power Cord (localized to region of sale)	✓	✓
Mounting Kit	Rack mount	Rack mount
Rubber footpads for tabletop installation	✓	✓
Installation Guide	✓	✓
Ordering Information		
GS724TP		
GS724TP-300AUS	Australia	
GS724TP-300EUS	Europe, including United Kingdom	
GS724TP-300INS	India	
GS724TP-300JPS	Japan	
GS724TP-300KOS	South Korea	
GS724TP-300NAS	North America, Latin America	
GS724TP-300PES	Middle East	
GS724TP-300PRS	China	
GS724TP-300TWS	Taiwan	
GS724TP-300UKS	Hong Kong	
GS724TPP		
GS724TPP-300AUS	Australia	
GS724TPP-300EUS	Europe, including United Kingdom	
GS724TPP-300INS	India	
GS724TPP-300JPS	Japan	
GS724TPP-300KOS	South Korea	
GS724TPP-300NAS	North America, Latin America	
GS724TPP-300PES	Middle East	
GS724TPP-300PRS	China	
GS724TPP-300TWS	Taiwan	
GS724TPP-300UKS	Hong Kong	

24-Port Gigabit PoE+ Smart Switch with 2 SFP Ports and Cloud Management

Ordering Information

Optional Modules and Accessories

AGM731F	SFP Transceiver 1000BASE-SX (Short range, multimode)
AGM732F	SFP Transceiver 1000BASE-LX (Long range, single mode)
AGM734-10000S	SFP Transceiver 1000BASE-T Copper RJ45 GBIC

* This product comes with a limited warranty that is valid only if purchased from a NETGEAR authorized reseller, and covers unmodified hardware, fans and internal power supplies – not software or external power supplies, and requires product registration at <https://www.netgear.com/business/registration> within 90 days of purchase; see <https://www.netgear.com/about/warranty> for details. Intended for indoor use only.

** The NETGEAR OnCall 24x7 contract provides unlimited phone and email technical support for your networking product. For ProSAFE products purchased prior to 06/2014, also includes next business-day hardware replacement.

† NETGEAR #1 in US Market Share according to NPD data for Unmanaged and Smart Switches, September 2019. NETGEAR #1 in Europe Market Share according to Context data for Unmanaged and Smart Switches, September 2019.

NETGEAR, the NETGEAR Logo, ProSUPPORT, ProSAFE and Virtually Anywhere are trademarks of NETGEAR, Inc. in the United States and/or other countries. Other brand names mentioned herein are for identification purposes only and may be trademarks of their respective holder(s).

NETGEAR, Inc. 350 E. Plumeria Drive, San Jose, CA 95134-1911 USA, 1-888-NETGEAR (638-4327), E-mail: info@NETGEAR.com, www.NETGEAR.com

D-GS724TP/GS724TPP-25Jan23