



Loudspeakers

Up 6

Two-way passive, full-range 6" ceiling speaker



Optimal Audio

FEATURES

- 6" Coaxial driver
- Discreet size
- Unobtrusive Design
- 8 ohm or 70/100V line operation
- Range of power taps
- Wide Conical Coverage Pattern
- Integrated Mounting Hardware

Up 6 is a no-compromise two-way, passive 6" ceiling speaker delivering consistent coverage and full frequency sound to a wide range of cost conscious, commercial environments that require higher sound pressure levels — from hotels and concourses to retail outlets, bars and restaurants.

An integral fixing system is included to achieve a simple and clean installation. Up 6 has a steel back can and perforated steel grille and is finished in neutral white.

Up 6 features a 6" (162mm) low frequency driver paired with a 0.7" (20mm) silk dome tweeter. It is suitable for both high quality speech and music

reproduction. A conical 110° coverage pattern ensures consistent, high performance sound where it needs to go.

Each Up 6 can be run on a variety of 70 or 100 volt taps, or at low impedance. The 16 ohm setting allows up to four units to be connected to each amplifier channel at low impedance. Tap selection is via a rotary switch behind the removable grille.

SmartAmps or Zone will provide optimal performance and loudspeaker protection. When coupled with the Zone series, a ZonePad and the WebApp makes setting up a system and end user control simple and intuitive.

APPLICATIONS



Cafes



Bars/
Restaurants



Retail



Wedding
Venues



Hotels



Education
Facilities



Houses of
Worship



Corporate
Offices




Museums



Fitness Studios



Residential






Loudspeakers

Up 6

Two-way passive, full-range 6" ceiling speaker



Optimal Audio



SPECIFICATIONS

TYPE	Two-way, full range, passive, ceiling speaker
FREQUENCY RESPONSE (with preset)	115Hz - 18kHz $\pm$ 3dB -10dB @ 80Hz
DRIVERS	LF: 6.5" (162mm), Coated paper HF: 1 (25mm) exit/0.7 (20mm) voice coil, Silk Dome
RATED POWER (AES)	60W
NOMINAL IMPEDANCE	16 Ohms
SENSITIVITY (1W/1m)	90dB
MAXIMUM SPL	108dB (cont), 111dB (peak)
CROSSOVER	2.7kHz passive
RECOMMENDED HIGH-PASS FILTER	24dB/octave @ 80Hz
TRANSFORMER TAPS @ 70V	60, 30, 15, 7.5W
TRANSFORMER TAPS @ 100V	60, 30, 15W
DISPERSION (-6dB)	110° conical
BACK CAN	Zinc-plated Steel
BAFFLE	ABS
PROTECTIVE GRILLE	Perforated steel
FIRE RATING	UL94-V0
CONNECTORS	2 inputs, 2 links, lockable, screwdown
FITTINGS	C-ring support backing plate
DIMENSIONS	(W) 251mm x (H) 205mm x (D) 251mm (W) 9.88" x (H) 8.07" x (D) 9.88"
WEIGHT	3.0kg (6.6lbs)
INCLUDED ACCESSORIES	2 tile support rails (for 2 ft or 600 mm tile spans), cutout template, paint shield, removable locking multi-pin connector
RECOMMENDED SUB	Sub 10



Paint Finish



Weight

optimal-audio.co.uk

© 2021. Optimal Audio Group Ltd.