

Lavalier

Lapel Microphone

AUSTRALIA

107 Carnarvon st, Silverwater NSW 2128 Australia
Ph: +61 2 9648 5855 Fx: +61 2 9648 2455

USA

PO Box 91028, Long Beach CA 90809-1028
Ph: +1 562 364 7400 Fax: +1 888 412 4664




Specifications

Acoustic Principle	Permanently Polarised Condenser
Active Electronics	JFET
Polar Pattern	Omni-directional
Frequency Range	60 Hz ~ 18 KHz
Output Impedance	3k Ω Typical
Signal To Noise Ratio	69 dB
Equivalent Noise	25 dB Typical
Clipping SPL	110 dB
Maximum Output	189 mV**
Sensitivity	-33.5 dB re 1 V/Pa (21 mV @ 94 dB SPL) $\pm$ 3 dB @ 1 kHz
Dynamic Range	85 dB Typical**
Power Requirements	Min 2 V ~Max 5 V through RØDE wireless adaptors P48 through RØDE XLR adaptor
Output Connection	RØDE Micon™ connector
Dimensions	Excluding packaging - $\varnothing$ 4.50 mm (wide) $\times$ 12 mm In clip: 12 mm (wide) $\times$ 28 mm $\times$ 22 mm (high)


Features

- Ultra discreet appearance
- Incorporated cable management system
- 4.5 mm miniature microphone
- Corrosion resistant stainless steel
- Low handling noise
- RØDE MiCon™ interconnectivity system provides interface with a wide range of wireless systems while maintaining discreet and unobtrusive appearance
- Gold plated connections

Polar Pattern



Frequency Response



Incl. Accessories

- Anti-trauma water resistant storage case
- Water resistant pop filter
- Mini-fur for high wind protection
- Shielded Kevlar® reinforced cable
- Lapel-style cable management clip
- Adjustment tools
- Sanitary cleansing wipes



Compact, interchangeable MiCon™ adaptors available to suit industry standard wireless systems. MiCon™ adaptors sold separately.