



DIS Digital Conference Systems
GM416/GM420/GM425
Gooseneck Microphones

GM416/GM420/GM425
Gooseneck Microphone



Description

GM series gooseneck microphones are compatible with Shure DCS6000 and DDS5900 conference units and feature Shure Microflex® capsules for high quality audio capture in meeting and conference spaces where communication is critical. Available in three lengths, each gooseneck microphone provides highly precise and flexible placement, with an integrated top LED light ring to indicate microphone activity. All variations also feature Shure CommShield® RF immunity, ensuring dependable, reliable performance regardless of venue.

Features

- Wide dynamic range and frequency response for accurate speech capture
- Cardioid polar pattern.
- Interchangeable Microflex cartridges provide the right polar pattern for every application
- Balanced, transformerless output With CommShield RF immunity to protect against electromagnetic hum and RF interference
- Snap-fit foam windscreen
- Available in 40 cm (15.7"), 50 cm (19.6") and 63 cm (24.8") lengths
- Compatible with all the DIS units featuring 3-pin socket for microphone connection including DC5980P, DC 6990P, DM 6680P and IS6132P

Specifications

Electrical

Microphone Type	Electret Cardioid
Frequency Response	50 Hz – 17 kHz
Sensitivity	–46 dB ± 3dB (0 dB = 1 V/1 Pa, 1 kHz)
Maximum SPL	110 dB SPL (3% THD)
Signal to Noise Ratio	>60 dBA
Front/Back Ratio	>25 dB (1 kHz)
Power Requirements	2–5 Volts DC Supplied from Conference Unit
Power Consumption	10 mA (typical)

Connectors

Connector Type	3 pin male
-----------------------	------------

Mechanical

Weight	GM416/C: 133 g GM420/C: 143 g GM425/C: 157 g
Length	GM416/C: 40 cm GM420/C: 50 cm GM425/C: 63 cm

Note: specifications subject to change

Certifications

The DCS 6000 system conforms to standard IEC 60914.

How To Order

Gooseneck microphone, 40 cm. Black with LED.	GM416/C
Gooseneck microphone, 50 cm. Black with LED.	GM420/C
Gooseneck microphone, 63 cm. Black with LED.	GM425/C
Windscreen for GM4xx gooseneck microphones. Pack of 4 pieces	RK513WS

SHURE®

United States, Canada,
Latin America, Caribbean:
Shure Incorporated
5800 West Touhy Avenue
Niles, IL 60714-4608 USA

Phone: +1 847-600-2000
Fax: +1 847-600-1212 (USA)
Fax: +1 847-600-6446
Email: info@shure.com
www.shure.com

Europe, Middle East, Africa:
Shure Europe GmbH
Jakob-Dieffenbacher-Str. 12,
75031 Eppingen, Germany

Phone: +49-7262-92490
Fax: +49-7262-9249114
Email: info@shure.de
www.shure.eu

Asia, Pacific:
Shure Asia Limited
22/F, 625 King's Road
North Point, Island East
Hong Kong

Phone: +852-2893-4290
Fax: +852-2893-4055
Email: info@shure.com.hk
www.shureasia.com