

Vi1000™

Soundcraft®
by HARMAN

96-CHANNEL COMPACT DIGITAL MIXING CONSOLE



HIGHLIGHTS ■

96 input channels with 24 mono/stereo mix busses

Plus LRC master busses

Unparalleled ease of use

With Vistonics II knobs-on-glass functionality and FaderGlow

SpiderCore™ integrated DSP engine

With BSS DPR901ii DEQ, vMIX automixing & Lexicon multiFX

Integrated Dante™ interface

Facilitates instant connection to industry standard Dante audio networks

Two expansion slots for optional I/O

For stagebox connection or option card installation

Wireless microphone monitoring

Shows battery and RF levels for AKG, Shure & Sennheiser systems

OVERVIEW ■

The Soundcraft Vi1000 sets a new standard in live mixing power and performance in a compact footprint. The console is the smallest member of the Vi-000 family, at just 86cm x 81cm (34" x 32") in size, yet it retains all the mixing and processing power of its two larger siblings, the Vi2000 and 3000. The Vi1000 is aimed at the live touring, install and corporate AV markets for applications where a highly compact, cost-effective but powerful console is required. Employing Soundcraft's unique and highly intuitive Vistonics II™ channel strip control interface, together with FaderGlow™, the console inherits the operating principles and workflows from the highly successful Vi3000, 5000 and 7000 consoles. In addition, it also integrates Soundcraft® SpiderCore™—a powerful integral DSP and I/O engine based on STUDER technology, offering 40-bit floating point processing for class-leading audio quality. The Vi1000 also comes into its own as an additional remote-controller surface for any of the larger consoles in the range, using the Mirroring feature.

KEY MESSAGES ■

PROCESSING

In addition to the standard gates and comps on all channel paths, audio processing includes the acclaimed BSS DPR901ii Dynamic EQ (8 instances) via an insertable processing pool which also includes 4 Lexicon Multi-effects and the ability to insert up to 64 external devices. STUDER vMIX automatic microphone mixing comes as standard and BSS 966 graphic EQs are available on all output busses.

COMPREHENSIVE I/O

The Vi1000 comes with rear panel local I/O featuring 16 mic/line inputs, 16 line outputs, and two 64ch expansion slots allowing up to two MADI-based stageboxes to be connected, or alternatively access to the extensive range of D21m I/O option cards, addressing all industry standard audio formats.

A built-in 64x64ch Dante/MADI interface provides direct recording/playback connection to any PC or Mac-based recording software, and allows the Vi1000 to integrate into an existing Dante network. The optical MADI interface allows an alternate record feed to MADI-based storage devices or connection to the

Soundcraft Realtime Rack Plug-in engine, adding a suite of Universal Audio UAD-powered plug-ins to the Vi1000's pristine audio quality. 4 channels of AES/EBU I/O complete the back panel, bringing the total I/O count to 212 in, 212 out. The 128 tie lines facility allows any I/O connector to be split or linked to any other.

SOFTWARE FEATURES

New with Vi1000 is compatibility with Sennheiser 6000-series wireless microphone systems, adding to the existing AKG WMS/DMS and Shure ULXD/QLXD monitoring and control functionality. This powerful feature allows users to see status of battery, RF and other parameters of connected microphones directly on the channel strips—in combination with vMIX dialogue Automixing and BSS Dynamic EQ, this makes Vi1000 an ideal tool for conferencing and theatre work.

Another new feature allows input channels to be easily spread across all of the Vi1000's 8 input and 8 output faders, giving easier handling of complex mixes.

Vi1000™

Soundcraft®
by HARMAN

96-CHANNEL COMPACT DIGITAL MIXING CONSOLE

APPLICATIONS ■

RENTAL COMPANIES
TOURING
CORPORATE A/V
MUSIC VENUE INSTALLATION

PHYSICAL SPECIFICATIONS ■

WEIGHT:

Vi1000 console only: 25kg (55lbs)

Vi1000 console incl. standard shipping carton: 46kg (102lbs)

DIMENSIONS: 84mm (3.2") x 803mm (31.6") x 351mm (13.8")

TECHNICAL SPECS ■

CONTROL SURFACE

Input Faders:

8 (16 when assigned to output faders)

Output Faders:

8 + 3 + 1

Total Faders:

20

Vistonics II screens:

2 (1 input, 1 master)

LOCAL I/O PHYSICAL CONNECTORS

Total I/O count:

212 in/212 out

Mic/Line Inputs:

16 Soundcraft HQ preamps

Line Outputs:

16

AES/EBU In (with SRC):

2 (4ch)

AES/EBU Out:

2 (4ch)

TB Mic in:

1 front panel with rear panel 48V on/off sw

Phones out:

1 stereo jack, under front armrest

Dante ports:

1x 64ch

MADI Optical:

64 in/64 out

D21m Option Slots:

2x double/4 single (total 128ch)

DSP MIXING CORE

Input Channels:

96 mono Pairable to 48 stereo

Busses - Aux/Grp:

24 mono or stereo

Busses - Matrix:

From bus pool – max 16 mono/stereo

Busses - Master:

3 (LRC)

Assignable Insert Points:

64 external + 8 DEQ + 4FX

Lexicon FX:

4 Stereo reverb/delay/pitch effects

BSS GEQ:

All mono/stereo busses and masters

BSS DPR901ii DEQ:

8 instances

vMIX Automixing:

2x16ch instances

EXTERNAL CONTROL PORTS

Ethernet:

1 (for Mirroring and external control)

MIDI:

1 In 2 Out

Mains Input:


2, switched, for redundant PSUs.

USB2.0:

4 (2 front, 2 rear)

Wordclock:

In /Out 2x BNC




Vi1000™

Soundcraft®
by HARMAN

96-CHANNEL COMPACT DIGITAL MIXING CONSOLE

PHYSICAL DIMENSIONS ■



© 2017 HARMAN International Industries, Incorporated. All rights reserved. Features, specifications and appearance are subject to change without notice.

www.soundcraft.com

SPEC SHEET