



ESiGO ESi200D

PROFESSIONAL ALL IN ONE PORTABLE SPEAKER



The SOUNDVISION ESiGO ESi200D Portable PA system is a completely self-contained mobile sound system which is battery powered 2-way active speaker 12-inch low-frequency driver, 3.5-inch Titanium driver Built-in rechargeable battery provides cordless sound. Includes UHF wireless microphone with Bluetooth connection for wireless audio streaming Built-in SD-Card USB (MP3/WMA) player for unattended playback Pole-mount socket, telescoping handle and transport wheels built in 5-band EQ and reverb effect 2 CH Mic XLR or 1/4" TR inputs.1 CH Line stereo RCA or 3.5mm TRS inputs. 2 CH UHF Wireless microphones and accessories.

Feature

- 2-Way active speaker system.
- 3.5"Titanium driver with 12" LF woofer.
- Frequency response: 50Hz – 20KHz.
- Power: 150W / 300W (max)
- Built-in Class D amplifier.
- Built-in : Media player
 - SD-Card / USB support MP3, WMA files.
 - Wireless audio streaming Bluetooth
 - LCD screen display.
 - IR Remote control.
- Built-in : Wireless microphone receiver.
 - Frequency range: 803.2MHz ,805.8MHz
 - Dual Handheld UHF wireless microphone.
- Built-in 5 channel mixer.
 - 2 CH Mic XLR or 1/4" TR inputs.
 - 1 CH Line stereo RCA or 3.5mm TRS inputs.
 - 2 CH UHF Wireless microphones.
- Built-in 5 band EQ with echo processor talk over.
- Built-in line output: RCA.
- Operating voltage AC: 100-240v DC: 12v
- Battery status indicator.
- Thermal protection for amplifier.
- Light-Weight plastic enclosure made from impact-resistant polypropylene (PP)
- Pole mount recess for 35mm tripods.
- Two wheels and retractable pulling handle for trolley-like mobility.



Verification of compliance : CE and RoHS

The ESiGO ESi200D conforms to standard



ESiGO esi2000

PROFESSIONAL ALL IN ONE PORTABLE SPEAKER

Specifications

Audio		
Speaker type.		2 Way full-range active speaker
Drivers.		LF 12" woofer, HF 3.5" titanium driver
Frequency response		50Hz-20KHz
Built-in mixer		5 channel
Power Output.		150W / 300W (Max)
Amplifier		Amplifier CLASS-D
Operating voltage		AC : 100-240V, DC : 12V
Media Player.		
SD-Card USB Port		Supported file formats: MP3, WMA
Bluetooth Version		Bluetooth 4.0
Bluetooth Range		10 Meter
Wireless microphone.		
Frequency range Group A		803.2MHz
Frequency range Group B		805.8MHz
Receivers		Dual UHF wireless receiver
Transmitters.		Dual Handheld microphone transmitters
Transmitter power.		10mw.
Distance Range.		50 Meter sing of line
Wireless Mic Power.		2 AA 1.5V batteries
Battery.		
Battery Type.		12V DC, 7Ah lead acid batteries
Battery life.		Up to 6-8 Hours at half power
Recharge Time.		Approximately 5 hours
General.		
Cabinet material.		ABS
Mounting Socket.		Standard 35 mm
Dimensions.		390 x 570 x 330 mm (W*H*D)
Weight.		18 Kg

SOUNDVISION™
PROFESSIONAL ALL IN ONE PORTABLE SPEAKER

