

S3 *passive*



S3-10



S3-15



S3-12



S3-15M

S3 *active*

S3 active Rear



15mm plywood

class D powered active models

1" throat compression drivers

durable unique effect paint finish

multiple M10 flying points

premium LF woofer and HF compression drivers

standby mode

35mm top-hat on 10/12/15 and 18 sub models

rear mount castors on 212/215 models

	S3-10	S3-12	S3-15	S3-15M	S3-212	S3-215	S3-18S
MAX SPL	127dB	128dB	130dB	130dB	134dB	135dB	132dB
PEAK	1200W	1400W	1600W	1600W	2800W	3200W	3200W
PGM	600W	700W	800W	800W	1400W	1600W	1600W
RMS	300W (250+50)	350W (300+50)	400W (350+50)	400W (350+50)	700W (620+80)	800W (720+50)	800W
WEIGHT	19kg	23kg	33kg	24kg	43kg	57kg	43kg
Cabinet type	2-way passive	2-way passive	2-way passive	2-way passive	2-way passive	2-way passive	passive sub woofer
Frequency response	60Hz - 18kHz	55Hz - 18kHz	45Hz - 18kHz	50Hz - 18kHz	50Hz - 18kHz	45Hz - 18kHz	35Hz - 250Hz
Sensitivity 1w@1m	96dB	97dB	98dB	98dB	99dB	100dB	97dB
Coverage (h x v)	90 x 50 degree	90 x 50 degree	90 x 50 degree	90 x 40 degree	80 x 60 degree	80 x 60 degree	-
Nominal Impedence	8 ohm	8 ohm	8 ohm	8 ohm	4 ohm	4 ohm	8 ohm
LF Driver	10" / 65mm VC	12" / 75mm VC	15" / 75mm VC	15" / 75mm VC	2x15" / 75mm VC	2x15" / 75mm VC	18" / 100mm VC
HF Driver	1.75" / 44mm VC	1.75" / 44mm VC	1.75" / 44mm VC	1.75" / 44mm VC	3" / 75mm VC	3" / 75mm VC	-
Crossover frequency	1.8kHz	2kHz	2kHz	2kHz	1.8kHz	1.8kHz	100Hz
Input connection	2 x NL4	2 x NL4	2 x NL4	2 x NL4	2 x NL4	2 x NL4	2 x NL4
Dimensions (wxhxd)	359 x 564 x 349mm	399 x 612 x 387mm	476 x 764 x 459mm	701 x 466 x 399mm	453 x 1007 x 433mm	542 x 1212 x 535mm	605 x 672 x 669mm

	S3-10A	S3-12A	S3-15A	S3-15MA	S3-212A	S3-215A	S3-18SA
MAX SPL	124dB	127dB	128dB	128dB	132dB	134dB	130dB
AMP PEAK	1440W	2040W	2040W	2040W	4400W	5200W	4000W
AMP PGM	720W	1020W	1020W	1020W	2200W	2600W	2000W
AMP RMS	360W (300+60)	510W (450+60)	510W (450+60)	510W (450+60)	1100W (1000+100)	1300W (1200+100)	1000W
WEIGHT	20kg	24kg	34kg	25kg	55kg	69kg	55kg
Cabinet type	2-way active	2-way active	2-way active	2-way active	2-way active	2-way active	active sub woofer
Frequency response	60Hz - 18kHz	55Hz - 18kHz	45Hz - 18kHz	50Hz - 18kHz	50Hz - 18kHz	45Hz - 18kHz	35Hz - 250Hz
Input sensitivity	-10dBv	-10dBv	-10dBv	-10dBv	-10dBv	-10dBv	0dBu
Coverage (h x v)	90 x 50 degree	90 x 50 degree	90 x 50 degree	90 x 40 degree	80 x 60 degree	80 x 60 degree	-
LF Driver	10" / 65mm VC	12" / 75mm VC	15" / 75mm VC	15" / 75mm VC	2x15" / 75mm VC	2x15" / 75mm VC	18" / 100mm VC
HF Driver	1.75" / 44mm VC	1.75" / 44mm VC	1.75" / 44mm VC	1.75" / 44mm VC	3" / 75mm VC	3" / 75mm VC	-
Crossover frequency	2.2kHz	2kHz	2kHz	2kHz	1.6kHz	1.7kHz	100Hz
Connection	XLR/JACK input XLR output	XLR/JACK input XLR output	XLR/JACK input XLR output	XLR/JACK input XLR output	XLR/JACK input XLR output	XLR/JACK input XLR output	XLR/JACK input XLR output
Dimensions (wxhxd)	359 x 564 x 349mm	399 x 612 x 387mm	476 x 764 x 459mm	701 x 466 x 399mm	453 x 1007 x 433mm	542 x 1212 x 535mm	605 x 672 x 669mm