

Technical specifications

	REVEAL 402	REVEAL 502	REVEAL 802
Frequency response ¹	56 Hz to 48 kHz	49 Hz to 43 kHz	42 Hz to 43 kHz
Maximum SPL ²	101 dB	108 dB	114 dB
Distortion	< 0.9 %	< 0.7 %	< 0.4 %
Dispersion (-6 dB)	90°	90°	90°
Drive Unit LF / Midrange	100 mm (4")	130 mm (5")	200 mm (8")
	Multi fibre paper cones		
Drive unit HF	19 mm (3/4") soft dome	25 mm (1") soft dome	25 mm (1") soft dome
Magnetic shielding	No	No	No
Max. operating temperature	35° C	35° C	35° C
Electronic section			
Inputs	Balanced XLR: 20 kΩ Unbalanced 6.35 mm (1/4") & 3.5 mm mini-jack: 10 kΩ		
Outputs	Monitor Link		
Input sensitivity	0.775 volt RMS for maximum output		
Crossover frequency	2.8 kHz	2.3 kHz	1.8 kHz
Amplifier output power	LF: 25 W RMS, HF: 25 W RMS	LF: 50 W RMS, HF: 25 W RMS	LF: 75 W RMS, HF: 25 W RMS
User controls	Power on/off; Volume; High Frequency Equalizer (+1.5 dB Boost, Neutral, -1.5 dB cut), Left/Right Monitor Select		
Power supply	100 to 120 V and 200 to 240 V (switchable), 50 to 60 Hz		
Power consumption	96 W maximum	120 W maximum	240 W maximum
Fuse	100 to 120 V, T800 mA/ 250 V	100 to 120 V, T1AL/ 250 V	100 to 120 V, T2AL/ 250 V

	REVEAL 402	REVEAL 502	REVEAL 802
	220 to 250 V, T400 mAL/ 250 V	220 to 240 V, T500 mAL/ 250 V	220 to 240 V, T1 AL/ 250 V
Cabinet			
Low frequency alignment	Optimized front port		
Cabinet construction	MDF cabinet with injection moulded front baffle		
Cabinet finish	Black fine texture		
Cabinet dimensions (H x W x D)	240 x 147 x 212 mm (9.45 x 5.79 x 8.35")	300 x 184 x 238 mm (11.81 x 7.24 x 9.37")	390 x 254 x 300 mm (15.35 x 10.00 x 11.81")

Notes

- 1: +/-3 dB measured at 1 m in an anechoic chamber.
- 2: Peak SPL at mix position for 1 pair driven.

Tannoy operates a policy of continuous research and development. The introduction of new materials or manufacturing methods will always equal or exceed the published specifications, which Tannoy reserve the right to alter without prior notice. Please verify the latest specifications with critical applications.