

D-CERNO AE

D-CERNO Central Unit: Quick, Easy & Hybrid



Description

The D-Cerno AE is the rack-based central engine that enables the D-Cerno discussion system for small to medium-sized meetings. By using state-of-the-art audio processing technology, D-Cerno AE is optimized for its market segment and ready to address future audio processing requirements. With this hybrid-ready control unit, D-Cerno offers unparalleled flexibility and makes integration with external systems easy.

D-Cerno occupies a unique position in the market since it combines an easy-to-setup system with a wide variety of interfaces. The central engine controls 50 delegate units and can be easily integrated by using USB audio, AES-67 and analog audio.

The delegate units are connected in daisy chain with a shielded CAT5E cable over the 4 bus connections (4 branches or 2 closed loops). With a loop, the redundancy mechanism guarantees that the system continues to function flawlessly if a cable should break or disconnect.

With the D-Cerno AE, organizing a hybrid meeting is as easy as plugging-in a USB cable. This will automatically create a speaker/microphone audio device on your PC which can be selected in your preferred meeting platform. This is combined with the new hands-free microphone mode which makes it possible to meet and discuss without the need to push a button

Integration with the D-Cerno AE is made easy with AES67 and the multi-channel USB connection which allows you to link your D-Cerno system with external devices such as a DSP or an external recording solution. With the integrated audio configurator, you can choose where the audio is routed to and group microphones and speakers together where necessary.

A simple interface gets you all controls right at your fingertips: a volume dial adjusts the volume, and a simple record button* starts or stops the recording. And with an integrated web server, operators have full control over the microphone modes and recording settings through an easy web interface.

D-Cerno AE can be mounted in a 19" rack but can also be simply positioned on a table for an easy setup. With its fan-less design, this engine is the center piece for all small to medium-sized meeting rooms without any concern for fan noise, even during extended usage.

The D-Cerno AE is able to record on an internal storage but also provides the possibility to record on a flash drive plugged in one of the two USB-C connections.

Benefits

- » Plug-and-play approach
- » 19" rack-based design
- » Hybrid ready via direct USB interface
- » Hands-free mode: No need to push a button
- » Easy to integrate with AES-67 and USB
- » Ready to record*
- » Smart Audio & Control:
 - › Dynamic Mix minus
 - › Gain sharing
 - › API control
- » Camera control integration capabilities
 - › T-Cam or 3rd Party
- » Fan-less operation
- » Extended power management*
 - › Wake-On-Lan
 - › Auto Power-on
 - › ECO mode

Features

- » Dynamics control
- » Integrated web server
- » Integrated recording capabilities
 - › Internal storage*
 - › External flash drive via USB-C*
 - › On a PC via multi-channel USB connection
- » Hands-free mode (16 microphones)
 - › With speaker detection*
- » DSP mode (8x8)
- » Fail-safe redundancy technology
- » For systems up to 50 units
- » System volume
- » Power button*
- » Recording button*
- » Secure API
- » IEEE802.1X*

Connectivity

- » 4 Bus connections (4 branches or 2 loops)
- » LAN connection (Control & AES-67)
- » 2x Lockable USB-C connections
 - › Flash drive interface*
 - › Hybrid meeting Interface
 - › Multi-channel audio interface
- » 2x Balanced XLR inputs
- » 2x Balanced XLR outputs
- » 1x Front-facing 3.5mm input jack
 - › Line or Microphone level*
- » 1x Front-facing 3.5mm output jack
 - › Line or Headphone level*
- » 1x Power connection

Specifications

Mechanical		
Material and color	Aluminium, Black (RAL 9011)	
Size (W x D x H)	48 x 17 x 4,5 cm	
Size packed (W x D x H)	57 x 42 x 6,4 cm	
Weight	3,36 kg	
Weight packed	2,48 kg (without PSU)	
Electrical		
Power supply external power adapter	External 100-240 VAC 50/60 Hz 2.5 A	
Power supply central unit	48 VDC 4.4 A	
Power supply output to power units	48 VDC 3.35 A Max 180 W	
Network - LAN		
Link speed	10/100 Mbps - 1 Gbps	
Security	802.1X* (MD5, TLS, PEAP-MSCHAPv2)	
Power control*	WoL	
Network - Conference		
Cable type	CAT 5E or better, shielded, SFTP, AWG 24, shielded RJ45 connector	
Max. length between units	80 m	
Max. length within loop	400 m	
Interfaces - Analog Audio Output	Balanced outputs (back)	Unbalanced output (front)
Signal level*	N/A	Line / Headphone
Number of interfaces	2	1
Connection type	XLR	3.5 mm jack
Max. Output level	+10 dBV	0 dBV
Load impedance	> 600 Ω	> 16 Ω
SNR (in dB A Weighted)	> 95	> 90
THD @ -10 dBV	< 0.01%	< 0.01%
Interfaces - Analog Audio Input	Balanced inputs (back)	Unbalanced input (front)
Signal level*	N/A	Line / Microphone
Number of interfaces	2	1
Connection type	XLR	3.5 mm jack
Max. input level	+10 dBV	0 dBV
Input impedance	> 10 KΩ	> 16 Ω
SNR (in dB A Weighted)	> 95	> 90

Interfaces - USB	Port 1	Port 2
Working modes	Audio device 1x1 (UAC2, 16 bit, 32 kHz) or Mass storage host *	Audio device 8x8 (UAC2, 16 bit, 32 kHz) or Mass storage host*
Power delivery	5 V - 0.5 A	
Power Sink	5 V - Sense only	
USB Version	USB 2.0	
Connector	USB-C	
Interfaces - Configuration Switches (*)	Function	
DIP 1	Disable auto start	
DIP 2	Disable front panel	
DIP 3	Wake on Lan	
DIP 4	ECO mode	
Audio Recording*		
Storage - Internal	3 GB	
Storage - External	USB flash drive (NTFS or FAT32)	
Format	MP3, WAV	
Quality	64, 128,196,256 kbps	
Environmental		
Operating temperature	5 - 45°C	
Regulatory		
Europe	CE	

* Available in future updates

Compatible Browsers

- » Google Chrome (version 124 or higher)
- » Microsoft Edge (version 124 or higher)

Compatible Products

- » **Discussion units**
 - » D-Cerno D-SL 71.98.0306
 - » D-Cerno C-SL 71.98.0307
 - » D-Cerno F-DM 71.98.0311
 - » D-Cerno F-CM 71.98.0312
- » **Spare Power Supply** **71.98.0340**
- » **D-Cerno Advanced License** **71.98.0360**
 - » Required for
 - » Multi-channel USB
 - » AES-67
 - » DSP Mode
 - » Custom audio routing
 - » Operator mode with microphone control

HQ Belgium

+32 51 30 30 45

conference@televic.com

<https://www.televic.com/en/conference>

Asia

+86 21 61 48 01 23

conference@televic.com

www.televic-conference.com.cn

France

+33 3 74 09 52 76

conference-france@televic.com

www.televic-conference.fr

United States

+1 916 920 0901

conference-us@televic.com

All information copyright Televic Conference, 2024.

Televic reserves the right to change this document without notice.

Version 1.4