

Education Projector

Vivitek DW882ST

For WXGA applications in a short-throw setting



- Bright 3,600 ANSI lumens with a high 15,000 contrast ratio
- Delivers up to a large 100" image from only 1.13m away from the projection surface
- Short throw projection allows presenter to stand in front of the screen without blocking image, casting shadows and eye glare
- DLP® and BrilliantColor™ technologies from Texas Instruments
- WXGA resolution with a maximum resolution up to WUXGA
- Assortment of connectivity options for easy connection to a variety of multimedia devices (HDMI 1.4b, VGA, S-Video, Composite Video, Audio-In/Out)
- 3D compatibility with DLP® Link™ and HDMI 1.4b Blu-ray technology support for dazzling and realistic life-like images
- 6 Segment (RYGCWB) colorwheel for accurate and detailed images
- New efficient lamp offers up to 7,000 hours of life (Dynamic Eco mode) for extended lamp life
- Sealed optical engine to keep dust out and improve performance
- Integrated audio speakers deliver 10W of total audio power
- Integrated network monitoring and management solutions (product certified) including Crestron® RoomView™, Extron, AMX SSDP and Telnet
- Anti-theft security features include: Kensington® security slot, security bar, and PIN lock keypad

Specifications

Display Type	Single 0.65" DLP Technology by TI
Brightness	3,600 ANSI Lumens
Native Resolution	WXGA (1280x800)
Maximum Resolution	WUXGA (1920x1200)@60Hz
Contrast Ratio	15,000:1
Lamp Life/Type	3500/5000/7000 Hours (Normal/Eco.Mode/ Dynamic Eco Mode), 240W/190W
Throw Ratio	0.52
Image Size (Diagonal)	70" - 100" (Best Size)
Projection Distance	0.779m - 1.127m (2.56ft ~ 3.71ft)
Projection Lens	F2.8 , f=7.51mm @ 87.2 inch
Zoom Ratio	Fixed
Aspect Ratio	16:10 Native
Offset (Vertical)	111.7% (±5%)
Keystone Correction	Vertical ±40 Degree; ±40 Steps
Horizontal Frequency	15, 31 - 91Hz
Vertical Scan Rate	24 - 30Hz, 47 - 120Hz
Lens Shift Range*	N/A
3D Compatibility	Yes (DLP® Link™, HDMI 1.4b (Blu-Ray))
Audio	10W (Mono)
Computer Compatibility	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA@60hz, Mac
Video Compatibility	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
I/O Connection Ports	HDMI v1.4b, VGA-In (x2), S-Video, Composite Video, Audio-In (Mini-Jack)(x3), VGA-Out, USB (Type A for 5V/1.5A Power Only), Audio-Out (Mini-Jack), RJ45, RS-232, Mini-USB (Service), Microphone (Mini-Jack), 12v Trigger
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock
Dimensions (WxDxH)	314 x 216 x 126mm (12.4" x 8.5" x 4.9")
Weight	3.17kg (7lbs)
Available Color	Two-Tone: White/Grey
Noise Level	36dB/32dB (Normal/Eco. Mode)
Power Supply	AC 110-240V, 50/60Hz
Power Consumption	260W (Eco. Mode), 320W (Normal Mode), <0.5W (Standby Mode), <6W (LAN Standby Mode)
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Lens Cap, Documentation Kit
Optional Accessories	Replacement Lamp

©2014 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.



Photos

