

Home Cinema Projector

Vivitek H1188

Full High-Definition Projection Primed for Home Cinema Viewing



Features

- Full high definition 1080p (1920x1080) resolution for the best quality, sharpness and clarity of a video
- High brightness of 2,000 ANSI lumens and high 50,000:1 contrast ratio ensuring a crisp and sharp image
- DLP® DarkChip3™ and BrilliantColor™ technologies for optimal black levels and vibrant colorful images
- Six segment RGBRGB color wheel for outstanding color reproduction
- VividMotion reduces fast-moving motion judder to create a fluid and flawless video stream
- Fine tune and optimize an image with advanced calibrations, including gamma and color management settings
- 2D to 3D conversion technology converts 2D content into 3D content from pretty much any video source or content
- MHL device compatibility for streaming of video and audio content from a compatible mobile device
- Vertical lens shift for greater installation convenience and flexibility
- Built-in 10W audio speaker for high quality audio playback
- Energy efficient lamps that last up to 5,000 hours (in dynamic eco. mode)
- Conveniently adjust the zoom and focus manually at the turn of a button
- Sealed engine to minimizing the impact of dust and smoke
- Top sided lamp cover for simple lamp removal and insertion
- Integrated Closed Caption Decoding (CCD) automatically converts the audio portion of a tv's signal and displays it as subtitles on the projected screen
- Anti-theft security features include: Kensington® security slot, security bar

Photos



Specifications

Display Type	Single 0.65" DLP® Technology by TI
Brightness	2,000 ANSI Lumens
Native Resolution	1080P (1920 x 1080)
Maximum Resolution	WUXGA (1920 x 1200) @60Hz
Contrast Ratio	50,000:1
Lamp Life/Type	3,000/4,000/5,000 Hours (Normal/Eco/Dynamic Eco. Mode) 260W/205W
Throw Ratio	1.39 - 2.09:1
Image Size (Diagonal)	25.9" - 324.9"
Projection Distance	1.2m - 10m (3.936ft to 32.8ft)
Projection Lens	F=2.418-2.97, f=20.7-31.05mm
Zoom Ratio	1.5x
Aspect Ratio	16:9
Offset	130% ±10%
Keystone Correction	±40 Degree; ±40 Steps
Horizontal Frequency	15, 31 ~ 91.4kHz
Vertical Frequency	24 ~ 30Hz, 47 ~ 120Hz
3D Functionality	Yes (Via DLP® Link™, Blu-ray 3D)
Speakers	10W (Mono)
Computer Compatibility	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA@60hz, Mac
Video Compatibility	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
I/O Connection Ports	HDMI v1.4, MHL/HDMI v1.4, VGA-In, Component (YPbPr RCA x 3), Composite Video, Audio-In (RCA), 12V-Trigger (Mini-Jack), RS-232C, 3D-Sync-Out, USB Power (5V, 1.5A), Mini-USB (Service)
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar
Dimensions (W x D x H)	286.3 x 272.2 x 128.1mm (11.2" x 10.7" x 5")
Weight	3.48kg (7.67lbs)
Available Color	Black
Noise Level	34dB/29dB (Normal/Eco Mode)
Power Supply	AC 100-240V, 50/60Hz
Power Consumption	310W (Normal Mode), 250W (Eco. Mode), <0.5W (Standby Mode)
Standard Accessories	AC Power Cord, HDMI Cable, Remote Control, Carry Case, Lens Cap, Documentation Kit
Optional Accessories	Replacement Lamp, Filter

©2015 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.

